ISSN:3049-0952
www.jsetms.com

DESIGN & THERMAL ANALYSIS OF 220CC OIL COOLED ENGINE CYLINDER HEAD BY DIFFERENT ALUMINUM ALLOYS

SAMBARI GOPINATH[1], Y. UMASHANKAR[2], Dr. P. SRINIVASULU[3]

[1]M.Tech Student, Department of Mechanical Engineering, Vaagdevi College of Engineering, Khammam - Warangal Hwy, Road, Bollikunta, Telangana 506005

[2]Associate Professor, Department of Mechanical Engineering, Vaagdevi College of Engineering, Khammam - Warangal Hwy, Road, Bollikunta, Telangana 506005

[3]Professor and Head of the Department of Mechanical Engineering, Vaagdevi College of Engineering, Khammam - Warangal Hwy, Road, Bollikunta, Telangana 506005

Abstract *The engine block is the linchpin of vehicles that run on internal combustion, providing the powerhouse for the vehicle. It is called a "block" because it is usually a solid cast car part, housing the cylinders and their components inside a cooled and lubricated crankcase.*

The main aim of the project is to analyze the thermal properties by varying geometry of cylinder block fins usingANSYSworkbench.The3Dmodelofthegeometries are created using CATIA and its thermal properties are analyzed using Ansys work bench 14.5. The variation of temperature distribution over time is of interest in many applications such as in cooling. The accurate thermal simulation could permit critical design parameters to be identified for improved life. Design off in plays an important role in heat transfer. There is a scope of improvement in heat transfer of air-cooled engine cylinder fin if mounted fin's shape varied from conventional one. Contact time between air flow and fin (time between air inlet and outlet flow through fin) is also important factor in such heat transfer.

1. INTRODUCTION

The internal combustion engine is an engine in which the combustion of a fuel (normally a fossil fuel) occurs with an oxidizer (usually air) in a combustion chamber. In an internal combustion engine, the expansion of the high-temperature and pressure gases produced by combustion applies direct force to some component of the engine, such as pistons, turbine blades, or a nozzle. This force moves the component over a distance, generating useful mechanical energy.

It is seen that the quantity of heat given to the cylinder walls is considerable and if this heat is not removed from the cylinders it would result in the resignation of the charge. In addition, the lubricant would also burn away, thereby causing the seizing of the piston. Excess heating will also damage the cylinder material. Keeping the above factors in view, itis observed that suitable means must be provided to dissipate the excess heat from the cylinder walls, so as to maintain the temperature below certain limits. However, cooling beyond optimum limits is not desirable, because it decreases the overall efficiency due to the following reasons: Thermal efficiency is decreased due to more loss of heat to the cylinder walls. The vaporization of fuel is less; this results in fall of combustion efficiency. Low temperatures increase the viscosity of lubrication and hence more piston friction is encountered, thus decreasing the mechanical efficiency. Though more cooling improves the volumetric efficiency, yet the factors mentioned above result in the decrease of overall efficiency. Thus, it may be observed that only sufficient cooling is desirable and any deviation from the optimum limits will result in the deterioration of the engine performance.



Engine cylinder fin

Fins

A fin is a surface that extends from an object to increase the rate of heat transfer to or from the environment by increasing convection. The amount of conduction, convection, radiation of an object determines the amount of heat it transfers. Increasing

ISSN:3049-0952
www.jsetms.com

The temperature difference between the object and the environment, increasing the convection heat transfer coefficient, or increasing the surface area of the object increases the heat transfer. Sometimes it is not economical or it is not feasible to change the first two options. Adding a fin to the object, however, increases the surface area and can sometimes be economical solution to heat transfer problems. Circumferential fins around the cylinder of a motor cycle engine and fins attached to condenser tube so fa refrigerator are a few familiar examples.



Fins

Objectives of the project

The following are the main objectives of the present work:

1. To design cylinder with fins for a 150cc engine by varying the geometry such as rectangular, circular and curve shaped (parabolic) with different materials and temperatures.
2. To determine the heat transfer coefficient with help of CFD analysis
3. To determine thermal properties of the proposed fin models.
4. To identify suitable alloy for the based on results obtained from finite element analysis and analytical method.

2. LITERATUREREVIEWS

KM Sajesh et al. [1] had studied that the heat lost by the body can be increased by increasing the surface area. The increment in surface area is done by creating holes of different sizes on the surface of fins. Increasing the diameter of hole created on the fin brings the overall temperature of the body lower than the lesser diameter model. By creating holes on fins the temperature of fins can be reduced. It also says that the turbulence of air also gets increased by creation on holes. This result came by performing a CFD analysis of rectangular fin engine made up with AL 6063 having thermal conductivity of 200W/mK. This CFD is done on steady state and transient state both. This also shows that; the transient temperature of all fins reached to the steady state temperature within 400 seconds of time.

V. Karthikeyan et al. [2] have founded that heat transfer rate of rectangular fin arrays is analyzed by design with perforated and with extension, analysis is carried out using ANSYS Workbench. In that steady state thermal analysis, temperature variations with respect to distance at which heat flow occur through the fin is analyzed. Heat transfer through fin arrays with rectangular extensions higher than that of fin with other type of fins compared to it. Temperature at the end of fin arrays with rectangular extensions is minimum as compare to fin with extensions, without extension and with perforated. Fin arrays with rectangular extensions provide near about 13 % to 21% more enhancement of heat transfer as compare to other type of fins. This result may vary for forced convection heat transfer.

L.Natrayanetal.[3] Design of fin plays an important role in heat transfer. There isa scope of improvement in heat transfer of air-cooled engine cylinder fin if mounted fin's shape varied from conventional one. Contact time between air flow and fin (time between air inlet and outlet flow through fin) is also important factor in such heat transfer. Wavy fin shaped cylinder block can be used for increasing the heat transfer from the fins by creating turbulence for upcoming air. Improvements in heat transfer can be compared with all the four model of the engine fins geometry by CFD Analysis and its flow characteristics are studied for all the geometries it is found that the curved fins provide better result when compared with all the other geometries.

3. METHODOLOGYUSED

ISSN:3049-0952
www.jsetms.com



Technical Specifications of Cylinder Block Used to Study

In the survey we have collected the information about the existing model by using sources like garages, service centers, research papers and web sources and we collected the all specifications of the existing design of the cylinder block. And the information collected in this survey is given below

Engine model: Bajaj pulsar
Engine type: Four-stroke, air-cooled,
Bore X stroke: 52.0 X 58.6 mm
Fuel system: Carburetor
Number of valves: 2
Displacementvolumes:150c.c.
Compression ratios: 12.2
Spark advance: 5 °/1500 rpm, 26 °/ 4500 rpm
Cylinder head material: Aluminum alloy (Thermalconductivity110-150 w/m k) Combustion chamber: Hemisphere shaped
Fin shape: Rectangular with curves at corner
Curve radius: R18
Finthickness':3.048
Tapper angle: 5*
Pitch of fin: Uneven

4. MATERIALPROPERTIESANDMODELING

Cast iron

Thermal conductivity=52w/mk
Specific heat=0.46 kj/kg k
Density =7200 kg/m^3

Aluminumalloy7475

Thermal conductivity=152w/mk
Specific heat=714j/kgk
Density =2810 kg/m^3

Alloy 6082

Thermal conductivity=180w/mk
Specific heat=900 j/kg k
Density=2700kg/m^3

MODELLING AND ANALYSIS OF CYLINDER FIN

Cylinder along with fin was modelled in CREO. The dimensions of the cylinder along with fin were taken from commercially available bike data sheet. Fins with different geometries (circular, Curved, aerodynamic and rectangular) were modelling using CREO Software



Figure. 3D models of Cylinder Fins, (a) Engine Cylinder 3D model with circular Fins (b) Engine Cylinder3DmodelwithrectangularFins(c)Engine Cylinder 3D model with aero dynamic Fins (d) Engine Cylinder 3D model with curved Fins

2ddrawing



CFD SIMULATION OF ENGINE CYLINDER FINS

ISSN:3049-0952
www.jsetms.com

Analysis of the cylinder fin for different geometries was carried out in ANSYS workbench. The basic model was generated using CREO and that model is imported to ANSYS work bench. Meshing is done in Ansys work bench.



Meshing models engine cylinder fins

Our next step in steady state CFD analysis is to generating mesh. The design using efficient mesh generation techniques, meshes were created with high contact sizing relevance. The total number of elements and nodes are19778 and 36988respectively.

CFDANALYSISRESULTS



Heat transfer coefficient for cylindrical fins engine



Heat transfer coefficient for rectangular fins engine



Heat transfer coefficient for aerodynamic fins engine



Heat transfer coefficient for curved fins engine

Materials used and properties

1. Cast iron

Thermal conductivity=52w/mk
Specific heat=0.46 kj/kg k
Density =7200 kg/m^3

2. Aluminumalloy7475

Thermal conductivity=152w/mk
Specific heat=714 j/kg k
Density=2810kg/m^3

3. Alloy 6082

Thermal conductivity=180w/mk
Specific heat=900 j/kg k
Density=2700kg/m^3

5. RESULTSANDANALYSIS

CASE:1 CylindricalFins



ISSN:3049-0952
www.jsetms.com



CASE:2 Rectangular fins





CASE:3 Aerodynamic fins





CASE:4 CurvedFins





6. CONCLUSIONS

The main aim of the project is to analyze the thermal properties by varying geometry of cylinder fins using Ansys work bench. The 3D model of the geometries are created using CREO and its thermal properties are analyzed using Ansys workbench 14.5. The variation of temperature distribution over time is of interest in many applications such as in cooling. The accurate thermal simulation could permit critical design parameters to be identified for improved life.

Design of fin plays an important role in heat transfer. There is a scope of improvement in heat transfer of

air cooled engine cylinder fin if mounted fin's shape varied from conventional one. Contact time between air flow and fin (time between air inlet and outlet flow through fin) is also important factor in such heat transfer. Curved fin shaped cylinder block can be used for increasing the heat transfer from the fins by creating turbulence for upcoming air. Improvements in heat transfer can be comparing with all the three models of the engine fins geometry by CFD Analysis and its flow

REFERENCES

[1] KM Sajesh, Neeleshsoni, Siddhartha Kosti, "Design Modification and Heat Transfer Analysis of Air-Cooled Rectangular Fin Engine", International Journal of Recent Scientific Research, Vol.7, Issue,3, pp.9653-9656, March,2016.

[2] V. Karthikeyan, R. Suresh Babu, G. Vignesh Kumar, "Design and Analysis of Natural Convective Heat Transfer Coefficient Comparison between Rectangular Fin Arrays with Perforated and Fin Arrays with Extension", International Journal of Science, Engineering and Technology Research, Volume 4, Issue 2, February 2015.

[3] L.Natrayan, G.Selvaraj, N.Alagirisamy, M.S.Santhosh, "Thermal Analysis of Engine Fins with Different Geometries", International Journal of Innovative Research in Science, Engineering and Technology, Vol. 5, Issue 5, May 2016.

[4] PardeepSingh, Harvinderlal, BaljitSinghUbhi, "Design and Analysis for Heat Transfer through Fin with Extensions", International Journal o Innovative Research in Science, Engineering and Technology, Vol. 3, Issue 5, May 2014.

[5] P. SaiChaitanya, B. Suneela Rani, K. Vijaya Kumar, "Thermal Analysis of Engine Cylinder Fin by Varying Its Geometry and Material", IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE) e ISSN:2278-1684, p-ISSN:2320-334X, Volume11, Issue6Ver.I(Nov-Dec.2014), PP37-44.

[6] Vignesh. P, P. SelvaMuthu Kumar, "Design, Modification and Analysis of Two-Wheeler Cooling Sinusoidal Wavy Fins", International Journal of Engineering Research & Technology (IJERT), ISSN: 2278-0181, Vol. 3 Issue 11, November-2014.

[7] Mohsin A. Ali, Prof. (Dr.) S.M Kherde, "Design Modification and Analysis of Two-Wheeler Cooling Fins", International Journal of Engineering and Applied Sciences, ISSN2305-8269, Vol.5No.01, June.2014.

[8] Sachin Kumar Gupta, Harishchandra Thakur, DivyankDubey, "Analyzing Thermal Properties of Engine Cylinder Fins by Varying Slot Size and Material", Open International Journal of Technology Innovations and Research, e-ISSN: 2321-1814, ISBN: 978-1-62951-946-3, Volume 14, April 2015.

[9] Hardik D. Rathod, Ashish J. Modi, Prof. (Dr.) Pravin P. Rathod, "Effect of Different Variables on Heat Transfer Rate of Four Stroke SI Engine Fins", International Journal of Mechanical Engineering and Technology (IJMET), ISSN 0976 – 6340(Print), ISSN 0976 – 6359(Online) Volume 4, Issue 2, March -April (2013) © IAEME.

[10] A Sathishkumar, MD Kathir Kaman, S Ponsankar, C Balasuthagar, "Design and Thermal Analysis on Engine Cylinder Fins by Modifying Its Material and Geometry", Journal of Chemical and Pharmaceutical Sciences, ISSN: 0974-2115, Volume 9 Issue 4, October - December 2016.

[11] K. Sathishkumar, K. Vignesh, N. Ugesh, P. B. Sanjeevaprasath4, S. Balamurugan, "Computational Analysis of Heat Transfer through Fins with Different Types of Notches", International Journal of Advanced Engineering Research and Science, ISSN: 2349-6495(P)|2456-1908(O), Vol-4, Issue-2, Feb-2017.

[12] Ajay Sonkar, Ishwar Singh Rajput, Jageshwar Dhruv, Kishore Kumar Sahu, "Comparative Thermal Analysis of Fin of I.C. Engine with Extensions", International Journal of Engineering Research & Technology, ISSN: 2278-0181, Vol. 6 Issue 04, April-2017.

[13] Deepak Gupta, Wankhade S.R., "Design and Analysis of Cooling Fins", International Journal on Mechanical Engineering and Robotics, ISSN (Print): 2321-5747, Volume-3, Issue-2, 2015.

[14] G. Angel, N. Sambasiva Rao, "Design and Analysis of Two-Wheeler Cooling Fins", International Journal of Engineering Science and Computing, Volume 6Issue No. 9, September 2016.

[15] Biermann, A. E. and B. Pinkel (1934). Heat Transfer from finned metal cylinders in an air stream, NACAReportNo.488

[16] J.C.Sanders, et al. (1942). Cooling test of an air-cooled engine cylinder with copper fins on the barrel, NACA Report E-103

ISSN:3049-0952
www.jsetms.com

[17] DenpongSoodphakdee, et al. (2001). "A Comparison of Fin Geometries for Heatsinks in LaminarForcedConvectionPart1 -Round, Elliptical, and Plate Fins in Staggered and In-Line Configurations. "The International Journal of Microcircuits and Electronic Packaging 24(1).
[18] Fernando Illan and M. Alarcon (2002). "Optimization of Annular Cylindrical and Spherical Fins in an Internal Combustion Engine under Realistic Conditions." Journal of Thermal Science and Engineering Applications 2.